



2025/2026

Bag inserter machine



Technical specifications

Sealing speed	360-480 Pcs/H
Packaging size	L2000*B1600*H2250mm
Power	380 V, 50 Hz, 6 kW
Air pressure	600 NL/min, 0,6–0,8 MPa
Height of the discharge table	600 mm
Machine dimensions	L 2000 × B 1600 × H 2250 mm



Technical specifications

Conveyor speed	360-480 Pcs/H
Bag size	L300-500*W300-400*H300-400mm
Power	380 V, 50 Hz, 6 kW
Air pressure	600 NL/min, 0,6–0,8 MPa, 600 mm
Height of the discharge table	600 mm
Machine dimensions	L 2120 × B 1800 × H 1950 mm



Technical specifications

Conveyor speed	1200-1500 PCS/H
Bag size	L300-500 × B300-400 × H300-400 mm
Power	380 V, 50 Hz, 8 kW
Air pressure	600 NL/min, 0,6–0,8 MPa
Height of the discharge table	650 mm
Machine dimensions	L 2200 × B 1900 × H 2200 mm



Technical specifications

Conveyor speed	360-500 Pcs/H
Bag size	L400-600 × B300-500 × H150-300 mm
Power	80 V, 50 Hz, 6 kW
Air pressure	600 NL/min, 0,6–0,8 MPa
Height of the discharge table	600 mm
Machine dimensions	L 2200 × B 1800 × H 1950 mm



HOME OF
PACKAGING

TBS PACK

 alpha-pack
group

 alpha-automatic

EIN SICHERES ZUHAUSE FÜR JEDES PRODUKT

alpha-pack GmbH | Otto-Hahn-Allee 1 | 50374 Erftstadt
+49-2235-79479-0 | info@alphapack.de | www.alphapack.de

