

Machine Series: TAPI

Container Capping Machines



Max. Sealing Diameter:
121 mm

Machine Information:

Our container capping machines use a non-contact process in which the internal seal is heated to finally hermetically seal plastic and glass containers. This sealing process takes place after filling and capping (with lids). The production capacity is up to 300 units per minute. Our container capping machines can also be used on fast conveyor belts, making them ideal for high speed packaging processes and the best choice for mass production.

Container

General Information:

- High capacity, best suited for mass production.
- High sealing capacity for continuous packaging processes
- Can be integrated into existing line or used separately



Model:	TAPI-2001A	TAPI-2001B	TAPI-3000A	TAPI-3000B
Voltage	220 V / 1 pH, 50 Hz	220 V / 1 pH, 50 Hz	220 V / 1 pH, 50 Hz	220 V / 1 pH, 50 Hz
Max. Power	2500 W	2500 W	3000 W	3000 W
Sealing Diameter	A: 15-45 mm B: 30-60 mm C: 50-120 mm	A: 15-45 mm B: 30-60 mm C: 50-120 mm	A: 30-60 mm B: 50-121 mm	A: 30-60 mm B: 50-121 mm
Max. Capacity	200	200	300	300
Cooling Method	Air Cooling	Air Cooling	Water Cooling	Water Cooling