



2025/2026

Tray sealing machines



Technical specifications

Machine dimensions	L1413 × B3169 × H1837 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	360–1200 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L1710 × B3680 × H1850 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	720–2400 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L1653 × B4438 × H1837 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	1440–4800 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L900 × B2890 × H1830 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	360–1200 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI 304
Certification	CE



Technical specifications

Machine dimensions	L1170 × B3600 × H1780 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	720–2400 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L1245 × B4255 × H1780 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	1440–4800 packages/hour
Power consumption	5,5 kW / 7 kW / 9 kW / 12 kW (depending on model)
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI 304
Certification	CE



1500 × 950 × 1450 h mm

Technical specifications

Machine dimensions	1500 × 950 × 1450 mm
Cycle rate	3–10 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h, 200 m ³ /h, 300 m ³ /h)
Packaging capacity	720–2400 packages/hour
Power consumption	5 kW
Power	240 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L732 × B1060 × H752 mm
Cycle rate	3–10 cycles/minute
Pump capacity	21 m ³ /h (optional: 45 m ³ /h)
Packaging capacity	360–1200 packages/hour
Power consumption	2 kW / 4 kW
Power	230/380 V
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L1050 × B800 × H600 mm
Cycle rate	10–12 cycles/minute
Pump capacity	440 × 280 mm
Packaging capacity	1200–1440 packages/hour
Power consumption	1,5 kW
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



1250 x 900 x 750 h mm

Technical specifications

Machine dimensions	L1250 × B900 × H750 mm
Cycle rate	10–12 cycles/minute
Pump capacity	100 m ³ /h (optional: 150 m ³ /h)
Packaging capacity	2400–2880 packages/hour
Power consumption	1,5 kW
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI 304
Certification	CE



Technical specifications

Machine dimensions	L740 × B667 × H1482mm
Cycle rate	2 cycles/minute (≈ 60–120 cycles/hour)
Pump capacity	21 m ³ /h
Packaging capacity	-
Power consumption	2,2kW
Power	230 V
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L840 × B667 × H1482mm
Cycle rate	2 cycles/minute (≈ 60–120 cycles/hour)
Pump capacity	45 m ³ /h (optional: 65 m ³ /h)
Packaging capacity	-
Power consumption	3 kW
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L740 × B767 × H1482mm
Cycle rate	2 cycles/minute (≈ 60–120 cycles/hour)
Pump capacity	45 m ³ /h (optional: 65 m ³ /h)
Packaging capacity	-
Power consumption	3 kW
Power	3P+N+PE, 380 V, 50 Hz
Material (outer casing)	Stainless steel AISI304
Certification	CE



Technical specifications

Machine dimensions	L465 × B352 × H320 mm
Cycle rate	ca. 3 seconds
Pump capacity	270 mm
Packaging capacity	-
Power consumption	1 kW
Power	230 V
Material (outer casing)	Stainless steel AISI304
Certification	CE



HOME OF
PACKAGING

TBS PACK

 alpha-pack
group

 alpha-automatic

A SAFE HOME FOR EVERY PRODUCT

alpha-pack GmbH | Otto-Hahn-Allee 1 | 50374 Erftstadt
+49-2235-79479-0 | info@alphapack.de | www.alphapack.de

